

# TERMINAL BLOCKS

## DOUBLE ROW TERMINAL BLOCKS



ITEM #	NUMBER OF TERMINALS	FRACTION DIMENSION	
		A	B
TB-3-2	2	1-13/32	1-1/8
TB-3-3	3	1-25/32	1-1/2
TB-3-4	4	2-5/32	1-7/8
TB-3-5	5	2-17/32	2-1/4
TB-3-6	6	2-29/32	2-5/8
TB-3-7	7	3-9/32	3
TB-3-8	8	3-21/32	3-3/8
TB-3-9	9	4-13/32	3-3/4
TB-3-10	10	4-13/32	4-1/8
TB-3-11	11	4-25/32	4-1/2
TB-3-12	12	5-3/32	4-7/8
TB-3-13	13	5-17/32	5-1/4
TB-3-14	14	5-29/32	6-3/8
TB-3-15	15	6-9/32	6
TB-3-16	16	6-21/32	6-3/8

ITEM #	NUMBER OF TERMINALS	FRACTION DIMENSION	
		A	B
TB-3-17	17	7-1/32	6-3/4
TB-3-18	18	7-13/32	7-1/8
TB-3-19	19	7-25/32	7-1/2
TB-3-20	20	8-5/32	7-7/8
TB-3-21	21	8-17/32	8-1/4
TB-3-22	22	8-29/32	8-5/8
TB-3-23	23	9-9/32	9
TB-3-24	24	9-21/32	9-3/8
TB-3-25	25	10-1/32	9-3/4
TB-3-26	26	10-25/32	10-1/2
TB-3-27	27	10-5/32	10-7/8
TB-3-28	28	11-5/32	10-7/8
TB-3-29	29	11-17/32	11-1/4
TM-3-30	30	11-29/32	11-5/8

Construction:	High Barrier Closed-back
Terminal Centers:	.375" (3/8") / 9.5 mm
UL Current Ratings:	20 amps
Voltage Rating, rms	
Class B: Comm 1 equip	250
Class C: Gen 1 ind 1	150
CSA Certified	300 @ 20 amps
Withstand Volts, DC	10,500
Insulator Material:	Thermoplastic, Glass-filled UL Temp Index 100°C UL Flame Retardant Rating 94V-0 Color - Black
Terminal Screws:	No. 6-32 x 1/4" Binding Head Screws Zinc-plated steel
Number of Terminals	2-30

